RIVKLE® – Standard blind rivet nuts - Stainless steel

Industrial markets are constantly changing, bringing new applications and new customer needs.
In order to support our customers and answer at best to their needs, Böllhoff has renewed and developed a dedicated stainless steel range.

RIVKLE® Stainless steel - Lubricated range

The lubricated range is based on standard products on which a lubricant has been applied to limit galling issues.
Customers don't need anymore to add manually any lubricant product (paste, spray, oil…).





Stainless steel | Thin head | Semi-hexagonal | Open

	d (mm)	L (mm)	B (mm)	e (mm) (min - max)	H +0,1/0 (mm)	S (mm)	L2 (mm)	E max (mm)		
M3	8,6	5,8	1,0 - 2,3	5,0	S=3,8-e	4,5	0,4	**343 98** 030 590	
	9,5		2,3 - 3,2		S=4,7-e			**343 98** 030 591	
M4	10,4	6,7	0,5 - 2,0	6,0	S=3,1-e	6,8	0,4	**343 48** 040 020*	**343 49** 040 506*
	11,3		0,8 - 3,0		S=4,2-e		0,3	**343 48** 040 030*	**343 49** 040 507*
	11,7	7,0	3,0 - 4,2		S=5,8-e	6,0	0,4	**343 98** 040 629*	
M5	12,0	7,8	0,5 - 3,0	7,0	S=4,4-e	7,0	0,45	**343 48** 050 020*	**343 49** 050 538*
	12,8	8,9	3,0 - 4,5		S=6,5-e	6,5	0,4	**343 98** 050 629	
M6	14,5	9,8	0,5 - 3,0	9,0	S=4,2-e	9,7	0,45	**343 48** 060 025	
	14,3	9,7					0,3	**343 98** 060 624*	**343 98** 060 637*
	16,5	10,2	3,0 - 5,5		S=7,4-e	8,7	0,45	**343 48** 060 055*	
	16,0	11,1	4,0 - 5,5		S=8,0-e	8,5	0,5	**343 98** 060 630	
M8	15,8	12,5	0,5 - 3,0	11,0	S=4,7-e	10,4		**343 48** 080 030*	**343 98** 080 631*
	17,1		1,5 - 5,0		S=7,0-e	10,2	0,3	**343 98** 080 625*	
M10	19,4	14,2	1,0 - 3,5	13,0	S=7,0-e	12,0	0,7	**343 48** 100 035	**343 49** 100 501
	21,5	14,4	2,5 - 5,5		S=9,1-e	12,5	0,65	**343 98** 100 691	
M12	23,5	17,4	1,0 - 4,5	16,0	S=8,5-e	15,0	0,7	**343 98** 120 501	

*Extra-flat thin head



Stainless steel | Thin head | Semi-hexagonal | Closed

	d (mm)	L (mm)	B (mm)	e (mm) (min - max)	H +0,1/0 (mm)	S (mm)	L2 (mm)	E max (mm)		
M3	13,3	5,8	1,0 - 2,3	5,0	S=3,8-e	9,0	0,4	**343 98** 030 592	
	14,2		2,3 - 3,2		S=4,7-e			**343 98** 030 593	
M4	15,4	6,7	0,5 - 2,5	6,0	S=3,8-e	11,5	0,4	**343 58** 040 025*	**343 59** 040 505*
	17,3	7,8	3,0 - 4,2		S=5,8-e			**343 98** 040 630	
M5	17,4	7,8	0,5 - 3,0	7,0	S=4,4-e	12,5	0,45	**343 58** 050 020*	**343 59** 050 505*
	20,3		3,0 - 4,5		S=6,5-e	13,4	0,5	**343 98** 050 683	
M6	20,5	9,8	0,5 - 3,0	9,0	S=4,1-e	15,0	0,6	**343 58** 060 030	**343 59** 060 587
	23,0	10,2	3,0 - 5,5		S=7,4-e	15,2	0,45	**343 58** 060 055*	
M8	26,6	12,5	1,5 - 5,0	11,0	S=7,0-e	19,0	0,3	**343 98** 080 629	
M10	29,3	15,6	1,0 - 3,5	13,0	S=7,0-e	22,0	0,65	**343 98** 100 692	
	31,3		2,5 - 5,5		S=9,0-e			**343 98** 100 693	
M12	34,0	18,9	1,0 - 4,5	16,0	S=8,5-e	26,4	0,7	**343 98** 120 502	

*Extra-flat thin head

Sales@RivetNutUSA.com
Request your quote with Rivet Nut USA (an operating division of Cardinal Components, Inc.)
Cardinal Components, Inc. is your authorized preferred specialty fastener distributor.
ISO 9001 CERTIFIED
www.RivetNutUSA.com
(800) 236-3200